PRODUCT FEATURES

COLOUR 1/4" CCD sensor.

* Auto Electronic Shutter (AES)

Built-in auto gain control (AGC) circuit. The colour cam-

era can achieve high guality images in low Lux conditions

Built-in auto electronic shutter function. The colour

0 Lux with IR LED ON. High guality IR LED's provide

camera's AES speed can reach 1/100.000s.

Camera Gamma characteristic is 0.45.

* Auto Gain Control (AGC)

* Gamma Characteristic

NTSC or PAL mode.

* Scanning Mode

* Night-time Vision

night-vision effect.

* Sensor (CCD)

CONNECTIONS

Monitor Video 12V DC VKFCB1 DC12V Power Supply Cable Cores Video Power

TROUBLE SHOOTING

1. No Picture after providing power

- . May be the power supply, please check the power supply voltage and polaritv.
- . Please check all the connecting cables to monitoring equipment, especially the 'BNC' connectors.

2. The picture shows 'rolling' interference ripples

- . May be caused by induced AC voltage on to video cables. Check for AC cables near video cables & move as necessary.
- . Check the earth potentials at monitor and peripheral equipments positions. Earth potentials should be the same at each position.

3. The picture background colour changes continuously

- . The fluorescent lamp's electromagnetic field causes colour roll. This is a normal phenomenon of the camera.
- . Reduce the fluorescent lamp numbers or increase the distance between the camera and the fluorescent lamps.

4. The picture 'smear's'

- . The power supply's voltage unstable.
- . Cables not connected correctly or have high impedance.

INTRODUCTION

Congratulations on your purchase of this FACINA product. This VKFCB1 is a high quality day / night camera with LED illumination, wide angle lens. & a sturdy cable managed mounting bracket.

The camera can be used indoors or outdoors & has a removable sun shield.

Please read this instruction manual carefully before installation to ensure correct use of the product.



To prevent fire or shock hazarded. Do not immerse the unit into water.

The symbol is intended to alert the user to the presence of important operating and maintenance (servicing) Instructions in the literature accompanying the appliance.



The symbol is intended to alert the user to the presence of uninsulated 'dangerous voltage' within the product's enclosure that may be of sufficient Magnitude to constitute a risk of electric shock to persons.



CAUTION: TO REDUCE THE RISK OF ELECTRIC

DO NOT REMOVE COVER OR BANCK NO USER SERVICEABLE PARTS INSIDE, REFER SERVICING

CAUTION:

зноск

To prevent electric shocks and risk of fire hazards. do NOT use other than specified power source.



- Please note the camera's operating temperature and its using environment requirement. Avoid using the camera at too high or too low temperatures. The operating temperature is -10°C-50°C. (Recommendatory operating temperature is -5°C--40°C.)
- Never position the camera to face the sun or bright object. This

may damage the CCD.

· Do not mount the camera by a radiator or heater.

- Notes :
- •Please ensure the correct specification power supply is used. Check voltage, polarity and operating temperature match the camera's reauirement.
- •Lightning protection is recommended for use with camera equipment. If not installed, in electrical storms, camera equipment should be disconnected.

Specification

Model	VKFCB1	
Pick Up Element	COLOUR 1/4"CCD	
Effective Picture Elements(H*V)	500×582	
Horizontal Resolution	420 TV Lines	
S/N Ratio	More than 48dB	
Clock Frequency (MHZ)	28.375	
Scanning System	2:1 interlace	
Minimum Illumination	0 Lux (with IR LED ON)	
Synchronous System Internal, Negative sync.		
Auto Electronic Shutter	1/50s~1/100,000s	
Gamma Characteristic	0.45	
IR Project Distance Up to 15 Meters (with 23 Unit Infrared		
IR Status	Under 10 Lux by CDS	
IR Power On	CDS Auto Control	
Video Output	1Vpp,75 Ω	
Auto Gain Control Auto		
Power/Current	12VDC(+/-10%)/ 300mA	
Lens	3.6 mm	
Dimension (mm)	50×85×60	
Weight (g)	220	
Storage Temperature	-30~ +60°C	
Operating Temperature	-10~ +45℃	

Packing List

No	Name	Model	Number
1.	Weather proof Day & Night IR Colour Camera	VKFC B1	1
2.	User Guide		1

FACINA

SURVEILLANCE

Distributed by

Audio Visual Security

4 Arkwright Court Fylde Industrial Estate Blackpool FY4 5DR

Tel: 01253 830904 Fax: 01253 830905 Email: enquiries.avs@adivision.co.uk Web: www.audiovisualsecurity.org.uk



VKFCB1

Weatherproof Day & Night IR Colour Camera



Notes: Please read this User Guide in detail prior to installation

Do not attempt to disassemble the camera. If the camera does not function correctly, please contact our technical helpline on Tel: 01253 792898 This document was created with Win2PDF available at http://www.win2pdf.com. The unregistered version of Win2PDF is for evaluation or non-commercial use only. This page will not be added after purchasing Win2PDF.